Architectural Door Accessories

Pemko Brush Gasketing

Applies to the following products:

45400_NB, 45250_NB, 45175_NB, 45061_NB, 45062_NB, 45041_NB, 35041_NB, 35061_NB

Installation Instructions

CUTTING BRUSH:

- 1. Remove brush prior to cutting.
- 2. Trim off excess brush using Lineman Side Cutting Pliers and crimp the brush filament ends.
- 3. Re-insert the brush until it is flush with one end of the retainer and crimp to hold in place.

PERIMETER GASKETING:

- 1. Can be installed on a wood or metal frame.
- 2. Measure, mark and trim header piece to length. Close door and position header piece on header stop so that seal makes light even contact with door. Mark header stop in center of slotted holes.
- 3. Drill pilot holes in header stop at marks.
- 4. Secure header piece to header stop with supplied screws.
- 5. To install the 2 jamb pieces, repeat steps 2, 3, and 4. Jamb pieces should contact threshold (or floor) at bottom & contact header piece at top.
- 6. Open and close door several times to check jamb weatherstrip fit and seal, and to make sure latch bolt engages strike plate.
- 7. To adjust, loosen screws, re-position weatherstrip, and tighten screws.

Tools Required:



www.pemko.com

MEMPHIS, TN USA P: 800 824-3018 F: 800 243-3656 VENTURA, CA USA VANCOUVER, BC CA P: 800 283-9988 P: 877 535-7888 F: 800 283-4050 F: 877 535-7444

TORONTO, ON CA P: 877 535-7888 F: 877 535-7444

Copyright © 2017 Pemko Manufacturing Co., an ASSA ABLOY Group company. All rights reserved. Reproduction in whole or in part without the express written permission of Pemko Manufacturing Company is prohibited.



The global leader in door opening solutions

Testing/Ratings:

Gasketing material for fire doors intended for aplication to listed steel frames and/or classified steel covered composite type, and hollow metal type fire doors rated up to 3 hours; wood and plastic covered composite type fire doors rated up to 1-1/2hours; and wood core type fire doors rated up to 20 minutes. (Thresholds may or may not contain gasketing material).



